

ACRYL MIX

Version 1.5

7/19/006

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company : BASF Wall Systems
3550 St. John's Bluff Rd. South
Jacksonville, FL 32224

Phone : 904-996-6000
Fax : 904-996-6130
Emergency contact : 1-800-424-9300

Productname : Finestone Acryl Mix
MSDS : 10692

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
------	---------------	------------	----------------------

No hazardous materials are present in this product above regulated levels as defined by 29 CFR 1910.1200.

(See Section 16 for abbreviation legend)

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause slight irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritaion.

EFFECTS OF OVEREXPOSURE - INHALATION: Slightly irritating to respiratory tract.

EFFECTS OF OVEREXPOSURE - INGESTION: Irritating to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No known components of this product are listed as known or suspected carcinogens per NIOSH, NTP, IARC, or OSHA.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION EYE CONTACT

ACRYL MIX

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eye with water for 15 minutes. Get medical attention.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into lungs.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: Non-Combustible

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: N.A.

EXTINGUISHING MEDIA: CO2 FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Repeat sorbent/sweep cycle until the spill has dried up. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Keep out of reach of children.

STORAGE: Keep container closed when not in use.

ACRYL MIX**SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection when the product is mixed or applied in a poorly ventilated area or if workplace levels of ingredients exceed the TLV. Follow applicable federal, state, and local regulations.

OTHER PROTECTIVE EQUIPMENT: Where contact is likely, wear chemical resistant gloves, chemical safety goggles with a face shield, and clean protective clothing to cover arms and legs to keep exposure to a minimum.

HYGIENIC PRACTICES: Do not take internally. Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: >212 F	VAPOR DENSITY	: Is heavier than air
ODOR	: Mild Acrylic	ODOR THRESHOLD	: N.D.
APPEARANCE	: liquid	EVAPORATION RATE:	Is slower than Butyl Acetate
SOLUBILITY IN H ₂ O	: Dilutable	SPECIFIC GRAVITY:	1.1 - 1.4
FREEZE POINT	: N.D.	pH @ 100.0 %	: 9.0 - 9.9
VAPOR PRESSURE	: N.D.	VISCOSITY	: N.D.
PHYSICAL STATE	: Liquid		
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.D.			

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Long term exposure to elevated temperatures.

INCOMPATIBILITY: Strong bases or oxidants. Strong Lewis or mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Acrid fumes. Oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

ACRYL MIX

SECTION 11 - TOXICOLOGICAL PROPERTIES

PRODUCT DERMAL LD50: No Information PRODUCT ORAL LD50: No Information
 PRODUCT LC50: No Information

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Review all local, state, and federal regulations concerning health and pollution for appropriate disposal procedures.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not Regulated

DOT TECHNICAL NAME: N.A.

DOT HAZARD CLASS: N.A.

HAZARD SUBCLASS: N.A.

DOT UN/NA NUMBER: N.A.

PACKING GROUP: N.A.

RESP. GUIDE PAGE:

DOT PLACARD AT: N.A.

DOT CLASS NUMBER: N.A.

UN PROPER SHIPPING NAME: Not Regulated

UN HAZARD CLASS: N.A.

UN CLASS NUMBER: AIR N.A.

MARINE N.A.

HAZARD SUBCLASS: AIR N.A.

MARINE N.A.

UN UN/NA NUMBER: N.A.

UN PACKING GROUP: AIR N.A.

MARINE N.A.

UN PLACARD AT: N.A.

ACRYL MIX

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Non-hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
None known.		

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----	CAS NUMBER
None Known.	

U.S. STATE REGULATIONS: AS FOLLOWS -

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
None known.	

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0
PERSONAL PROTECTION: B

PREVIOUS MSDS REVISION DATE: 06/15/98

REASON FOR REVISION: Manufacturer change. Revise to 16 section format.

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.04 lbs/gal, 4 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

ACRYL MIX

DISCLAIMER

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the Manufactures knowledge, or is obtained from sources believed by the Manufacture, Inc. to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The Manufacture assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the Manufacture assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

<END OF MSDS>