

FINEMASTIC

Version 1.3

06/30/06

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company : BASF Wall Systems
3550 St. John's Bluff Road, South
Jacksonville, FL 32224 ,

Phone : 904-996-6000
Fax :
Emergency contact : 1-800-424-9300

Productname : FINEMASTIC
MSDS : 10796

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	Crystalline silica	14808-60-7	1.0 %
02	Mineral spirits [Stoddard type]	8052-41-3	5.0 %

ITEM	EXPOSURE LIMITS				COMPANY	SKIN
	ACGIH		OSHA			
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	
01	.05 mg/m3	N.E.	.05 mg/m3	N.E.	N.E.	NO
02	100 ppm	N.E.	525 mg/m3	N.E.	N.E.	NO

(See Section 16 for abbreviation legend), * - Ceiling Value

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Substance may cause slight skin irritaion.

EFFECTS OF OVEREXPOSURE - INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: May cause irritation.

FINEMASTIC

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: This product contains solvents. reports associate repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Reports also indicate that solvents cause liver damage, kidney damage, and mucous membrane irritation. Be warned that intentional misuse by deliberately inhaling the vapors and/or the product contents (a process often called "sniffing") may be harmful or fatal. Preexisting respiratory or skin condition(s) may be aggravated by exposure. This product contains silicon dioxide [quartz] which has been listed as a suspected human carcinogen by NTP and IARC. Repeated or prolonged over exposure to free silica may cause silicosis or other delayed and serious lung injury. No exposure to crystalline silica anticipated with normal use of product.

PRIMARY ROUTE(S) OF ENTRY: INHALATION INGESTION EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eye with water for 15 minutes. Get medical attention.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into lungs.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: >200 F

LOWER EXPLOSIVE LIMIT: N.D. %

UPPER EXPLOSIVE LIMIT: N.D. %

AUTOIGNITION TEMPERATURE: N.D.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Solid stream of water or foam may cause frothing.

FINEMASTIC

SECTION 5 - FIRE FIGHTING MEASURES

SPECIAL FIREFIGHTING PROCEDURES: Containers exposed to fire should be kept cool with water spray. Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Repeat sorbent/sweep cycle until the spill has dried up. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Use only in a well ventilated area. Keep out of reach of children. If user operations generate dust, fume, or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

STORAGE: Keep container closed when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection when the product is mixed or applied in a poorly ventilated area or if workplace levels of ingredients exceed the TLV. Follow applicable federal, state, and local regulations.

OTHER PROTECTIVE EQUIPMENT: Where contact is likely, wear chemical resistant gloves, chemical safety goggles with a face shield, and clean protective clothing to cover arms and legs to keep exposure to a minimum.

HYGIENIC PRACTICES: Do not take internally. Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing.

FINEMASTIC

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : N.D. VAPOR DENSITY : Is heavier than air
 ODOR : N.D. ODOR THRESHOLD : N.D.
 APPEARANCE : Pigmented liquid EVAPORATION RATE: Is slower than Butyl
 SOLUBILITY IN H2O : Dilutable Acetate
 FREEZE POINT : N.D. SPECIFIC GRAVITY: 2.65 - 4.0
 VAPOR PRESSURE : N.D. pH @ 100.0 % : N.D.
 PHYSICAL STATE : Liquid VISCOSITY : N.D.
 COEFFICIENT OF WATER/OIL DISTRIBUTION: N.D.

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Long term exposure to elevated temperatures.
 INCOMPATIBILITY: Strong bases or oxidants. Strong Lewis or mineral acids.
 HAZARDOUS DECOMPOSITION PRODUCTS: Acrid fumes. Oxides of carbon.
 HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.
 STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

PRODUCT DERMAL LD50: No Information PRODUCT ORAL LD50: No Information
 PRODUCT LC50: No Information

COMPONENT TOXICOLOGICAL INFORMATION:

----- CHEMICAL NAME -----	-- DERMAL LD50 --	--- ORAL LD50 ---	----- LC50 -----
Crystalline silica	No Information	No Information	No Information
Mineral spirits [Stodda	No Information	> 5 g/kg	>5500mg/m3/4H

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Review all local, state, and federal regulations concerning health and pollution for appropriate disposal procedures.

FINEMASTIC

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not Regulated

DOT TECHNICAL NAME: N.A.

DOT HAZARD CLASS: N.A. HAZARD SUBCLASS: N.A.

DOT UN/NA NUMBER: N.A. PACKING GROUP: N.A. RESP. GUIDE PAGE:

DOT PLACARD AT: N.A.

DOT CLASS NUMBER: N.A.

UN PROPER SHIPPING NAME: Not Regulated

UN HAZARD CLASS: N.A.

UN CLASS NUMBER: AIR N.A. MARINE N.A.

HAZARD SUBCLASS: AIR N.A. MARINE N.A.

UN UN/NA NUMBER: N.A. UN PACKING GROUP: AIR N.A. MARINE N.A.

UN PLACARD AT: N.A.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN
None known.

FINEMASTIC

SECTION 15 - REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----	CAS NUMBER
None known.	

U.S. STATE REGULATIONS: AS FOLLOWS -

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
Crystalline silica	14808-60-7
Formaldehyde	50-00-0
Acrylonitrile	107-13-1
ethylene oxide	75-21-8
lead	7439-92-1
arsenic	7440-38-2
cadmium	7440-43-9
1,4-Dioxane	123-91-1

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0
PERSONAL PROTECTION: E

PREVIOUS MSDS REVISION DATE: 06/15/98

REASON FOR REVISION: Manufacturer change. Revise to 16 sections.

VOLATILE ORGANIC COMPOUNDS (VOCS): 1.39 lbs/gal or 137 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

FINEMASTIC

DISCLAIMER

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of The Manufacture's knowledge, or is obtained from sources believed by The Manufacture to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The Manufacture assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, The Manufacture assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

<END OF MSDS>