

SANDED PRIMER

Version 1.1

06/30/06

1. COMPANY AND PRODUCT INFORMATION

Company : BASF Wall Systems
 3550 St. John's Bluff Road, South
 Jacksonville, FL 32224 ,

Phone : 904-996-6000
 Fax :
 Emergency contact : 1-800-424-9300

Productname : SANDED PRIMER
 MSDS : 10891

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	Crystalline silica	14808-60-7	25.0 %
02	ethylene glycol	107-21-1	5.0 %

ITEM	EXPOSURE LIMITS					
	ACGIH		OSHA		COMPANY	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	.05 mg/m3	N.E.	.05 mg/m3	N.E.	N.E.	NO
02	N.E.	127 mg/m3*	N.E.	125 mg/m3		NO

(See Section 16 for abbreviation legend), * - Ceiling Value

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Substance may cause slight skin irritaion.

EFFECTS OF OVEREXPOSURE - INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: May cause irritation.

SANDED PRIMER

SECTION 3 - HAZARDS IDENTIFICATION CONT'D

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Chronic overexposure may cause kidney damage. This product contains silicon dioxide [quartz] which has been listed as a suspected human carcinogen by NTP and IARC. Repeated or prolonged over exposure to free silica may cause silicosis or other delayed and serious lung injury. No exposure to crystalline silica anticipated with normal use of product.

PRIMARY ROUTE(S) OF ENTRY: INHALATION INGESTION EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eye with water for 15 minutes. Get medical attention.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into lungs.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: >200 F
LOWER EXPLOSIVE LIMIT: N.D. %
UPPER EXPLOSIVE LIMIT: N.D. %

AUTOIGNITION TEMPERATURE: N.D.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Solid stream of water or foam may cause frothing.

SPECIAL FIREFIGHTING PROCEDURES: Containers exposed to fire should be kept cool with water spray. Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

SANDED PRIMER

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Repeat sorbent/sweep cycle until the spill has dried up. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Use only in a well ventilated area. Keep out of reach of children. If user operations generate dust, fume, or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

STORAGE: Keep container closed when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection when the product is mixed or applied in a poorly ventilated area or if workplace levels of ingredients exceed the TLV. Follow applicable federal, state, and local regulations.

OTHER PROTECTIVE EQUIPMENT: Where contact is likely, wear chemical resistant gloves, chemical safety goggles with a face shield, and clean protective clothing to cover arms and legs to keep exposure to a minimum.

HYGIENIC PRACTICES: Do not take internally. Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: N.D.	VAPOR DENSITY	: Is heavier than air
ODOR	: None	ODOR THRESHOLD	: N.A.
APPEARANCE	: Pigmented liquid	EVAPORATION RATE:	Is slower than Butyl
SOLUBILITY IN H2O	: Dilutable		Acetate
FREEZE POINT	: N.D.	SPECIFIC GRAVITY:	2.71
VAPOR PRESSURE	: N.D.	pH @ 100.0 %	: N.D.
PHYSICAL STATE	: Liquid	VISCOSITY	: N.D.
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.D.			

(See Section 16 for abbreviation legend)

SANDED PRIMER

SECTION 14 - TRANSPORTATION INFORMATION CONT'D

DOT PLACARD AT: N.A.
DOT CLASS NUMBER: N.A.
UN PROPER SHIPPING NAME: Not Regulated
UN HAZARD CLASS: N.A.
UN CLASS NUMBER: AIR N.A. MARINE N.A.
HAZARD SUBCLASS: AIR N.A. MARINE N.A.
UN UN/NA NUMBER: N.A. UN PACKING GROUP: AIR N.A. MARINE N.A.
UN PLACARD AT: N.A.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -
OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:
This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD

SARA SECTION 313:
This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
ethylene glycol	107-21-1	5.0 %

TOXIC SUBSTANCES CONTROL ACT:
This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----	CAS NUMBER
None known.	

SANDED PRIMER

SECTION 15 - REGULATORY INFORMATION CONT'D

U.S. STATE REGULATIONS: AS FOLLOWS -

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
Crystalline silica	14808-60-7
Formaldehyde	50-00-0
Benzyl chloride	100-44-7
ethylene oxide	75-21-8
lead	7439-92-1
arsenic	7440-38-2
cadmium	7440-43-9

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0
PERSONAL PROTECTION: E

PREVIOUS MSDS REVISION DATE: 06/16/98

REASON FOR REVISION: Manufacturer change. Revise to 16 sections.

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.91 lbs/gal or 109 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

SANDED PRIMER

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of SKW-MBT Operations's knowledge, or is obtained from sources believed by SKW-MBT Operations, Inc. to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. SKW-MBT Operations, Inc. assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, SKW-MBT Operations, Inc. assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

<END OF MSDS>
